


Leica SmartWorx Field Software



Standard features

Operation

Always in view status information bar
 Permanent display of current positioning accuracy
 Data import: ASCII, DXF, GSI, DTM models
 Data export: Custom ASCII, DXF, XML, Raw data
 Field-to-Office data transfer using ftp

Setup Reference

Configuration of RTK base station for operation without requiring a controller
 Selection of antenna type
 Selection of radio channel
 Computation of navigated base position

GPS Resection

Provides a rapid localisation of a GPS job
 Positions onto existing control points
 Uses a similar method as a TPS resection
 Requires no knowledge of coordinate systems

Determine Coordinate Systems

For the conversion of GNSS positions to local coordinates
 Provides a Onestep, Twostep or Classic 3D transformation type
 One point localisation for rapid calibration
 Display and recording of parameters and residuals
 Automatic matching of measured and entered points

Coordinate Geometry

Inverse, intersections, line and arc related computations
 Calculations made from entered or measured points
 Graphical plot view of computations
 Coding of calculated points
 Immediate stakeout of calculated points

Survey

Manual or automated point measurement
 Configurable display layout
 Point, line, area or free coding
 Smart and Quick coding
 Measuring of hidden points using offset data

Stakeout

Orientation to north, point, line, sun or by arrow
 Quality comparison between stake and design
 Automatic selection of closest design point
 Graphical selection of point from map display
 Design height editing during stakeout

Optional features

Reference Line

Staking of line, arcs and polylines
 Staking of chainages
 Staking of slopes
 Quality comparison between stake and design
 Graphical display of design

RoadRunner

Staking of alignments:
 Stringlines, single/double cross slopes, batters, surfaces
 Graphical staking and quality control
 Alignments can be created in the field
 Importing of alignments from various design formats
 Comprehensive field report of completed work

Volume Calculations

Computation of surface areas and volumes
 Using imported or measured points
 Graphical display of triangles
 DXF export of measured surfaces
 Comprehensive reporting

DTM Stakeout

Staking out of heights based on a digital terrain model
 Staking out of points with heights taken from the DTM
 Various DTM layers can be selected for stakeout
 Can be used for quality control of design surface

Functionality Options

GLONASS satellite tracking
 Raw data logging for post-processing
 RTK functionality with unlimited baseline length
 Position and display update rate of 5 Hz (0.2 sec)
 Reference network access (includes unlimited baseline)
 RTCM/CMR RTK data messages input
 Bluetooth® mobile phone connection



Leica GS09 GNSS Datasheet



GS09 SmartAntenna

The SmartAntenna can be used in a large variety of operating modes, providing you with a complete surveying system.

- RTK Rover – exceptionally rugged and light weight pole setup without any cables
- Reference Station – easily setup RTK base station operates without controller
- Network Rover – a complete surveying system, operating in all reference networks
- SmartStation – the GS09 fits onto a TPS creating one easy-to-use instrument



CS09 Controller

The Leica CS09 controller is designed to suit any surveying task with a wide range of functionality and application programs.

- Ergonomic – QWERTY alphanumeric keyboard and function keys for rapid data entry
- Colour Display – large display with touch screen functionality
- Removable Memory – up to 1 GB data storage on CompactFlash card



SmartWorx Field Software

SmartWorx is based on the proven and familiar operating concept of the Leica System 1200.

- Icon-based Menus – quick to learn, ensuring instant productivity
- Application Programs – enable any survey task to be easily and efficiently completed
- Field-to-Office – transfer data between the work site and the office computer
- Plug & Play – automatic detection of communication devices for easy setup

Swiss Technology
by Leica Geosystems



Total Quality Management –
our commitment to total
customer satisfaction.

The Bluetooth® word mark and logos are owned by Bluetooth SIG, Inc. and any use of such marks by Leica Geosystems AG is under license.

Illustrations, descriptions and technical data are not binding. All rights reserved. Printed in Switzerland – Copyright Leica Geosystems AG, Heerbrugg, Switzerland, 2009. 774769en – VIII.09 – RDV

Leica Geosystems AG
Heerbrugg, Switzerland
www.leica-geosystems.com

- when it has to be right







- when it has to be right






Leica GS09 Antenna



GNSS Technology 	Measurement Engine		
	Leica patented SmartTrack+ technology	<ul style="list-style-type: none"> Jamming resistant measurements High precision pulse aperture multipath correlator Excellent low elevation tracking technology Very low noise GNSS carrier phase measurements with <0.5 mm precision Minimum acquisition time 	
	No. of channels	120 channels	
	Reacquisition time	< 1 sec	
GNSS Measurements			
Satellite signals tracking	GPS: L1, L2, L2C (C/A, P, C Code) GLONASS: L1, L2 (C/A, P narrow Code)		
Measurement Performance 	Accuracy ¹		
	DGPS/RTCM	Typically 25 cm (rms)	
	RTK Rapid static (phase) Static mode after initialization	Horizontal: 5 mm + 0.5 ppm (rms) Vertical: 10 mm + 0.5 ppm (rms)	
	RTK Kinematic (phase) Moving mode after initialization	Horizontal: 10 mm + 1 ppm (rms) Vertical: 20 mm + 1 ppm (rms)	
	Post Processing (phase) Static with long observations	Horizontal: 3 mm + 0.5 ppm (rms) Vertical: 6 mm + 0.5 ppm (rms)	
	Post Processing (phase) Rapid static mode	Horizontal: 5 mm + 0.5 ppm (rms) Vertical: 10 mm + 0.5 ppm (rms)	
	On-The-Fly initialization		
	Reliability	Better than 99,99% using Leica SmartCheck+ technology	
	Time for initialization	Typically 8 sec ²	
	RTK baseline range	up to 50 km	
	Hardware 	User Interface	
		Keys	On / Off key
Led Status indicator		Satellite tracking, <i>Bluetooth</i> [®] communication and battery power	
Communication ports		<ul style="list-style-type: none"> Combined USB / Power port with 8-pin Lemo plug Integrated <i>Bluetooth</i>[®] port 5-pin clip on contacts for Leica SmartStation setup 	
Physical			
Weight		1.05 kg including battery	
Dimension (diameter x height)		186 mm x 89 mm	
Environmental specifications			
Temperature, operating		-40° C to +65° C (-40° F to +149° F) ³	
Temperature, storage		-40° C to +80° C (-40° F to +176° F) ³	
Humidity		100% ⁴	
Sealed against water		IP67: Temporary submersion into water (max. depth 1 m)	
Sealed against sand and dust		Dust tight, protection against blowing dust	
Vibration		Withstands vibrations in compliance with ISO9022-36-08	
Drops		Withstands 1 m drop onto hard surface	
Topple over		Withstands topple over from a 2 m survey pole onto hard surface	
Functional shock		No loss of lock to satellite signals when used on a pole setup and submitted to pole bumps up to 150 mm	
Power management			
Supply Voltage		Nominal 12 V DC, Range 10.5 – 28 V DC	
Power consumption		Typically: 1.8 W, 150 mA	
Internal Power supply		Removable & rechargeable Li-Ion battery, GEB211 2.2 Ah / 7.4 V or GEB212 2.6 Ah / 7.4 V	
Operation time		Up to 7 hours using GEB212 battery ⁵	
Communications 	RTK transmission		
	Source	Direct from GS09 (No datalogger required)	
	RTK format	Leica Lite proprietary format	
	Radio Modems	All Satellite and Pacific Crest radios in GFU or standard housing	
	Integration with TPS		
	SmartStation functionality	Connects to Leica TPS1200, TS30 and TM30 instruments	

Leica CS09 Controller



User Interface 	Standard software	
	Operating system	Microsoft Windows CE 5.0 software
	Application software	Leica SmartWorx field software
	Terminal software	Leica GX1200 sensor control
	Software control	
	Display	¼ VGA colour, graphics capable
	Touch screen	Toughened film on glass
	Keyboard	62 keys with QWERTY alphanumeric & function keys
	Illumination	Backlight illuminated display and fully illuminated keys
	Hardware 	Physical
Dimension		218 mm x 123 mm x 47 mm
Weight of CS09		740 g including battery
Weight of pole setup		3.47 kg for complete rover pole setup
Weight of network rover		2.85 kg for complete network rover using a <i>Bluetooth</i> [®] mobile phone
Interfaces		
Data storage		Removable CF card (256 MB and 1 GB available)
Communication ports		<ul style="list-style-type: none"> Combined USB/Power port with 8-pin Lemo plug 2 x <i>Bluetooth</i>[®] ports Class 2 7-pin clip on contacts for GHT56 SmartHolder connection
Environmental Specifications		
Temperature, operating		-30° C to +65° C (-22° F to +149° F) ³
Temperature, storage		-40° C to +80° C (-40° F to +176° F) ³
Humidity		100% ⁴
Sealed against water		IP67: Temporary submersion into water (max. depth 1 m)
Sealed against sand and dust		Dust tight, protection against blowing dust
Drops		Withstands 1.5 m drop onto hard surface
Vibration	Withstands vibrations in compliance with ISO9022-36-08	
Power Management		
Supply Voltage	Nominal 12 V DC, Range 11.5 – 28 V DC	
Power consumption	Typically: 1.4 W, 120 mA	
Internal Power supply	Removable & rechargeable Li-Ion battery, GEB211 2.2 Ah / 7.4 V or GEB212 2.6 Ah / 7.4 V	
Operation time:	Up to 13 hours using GEB212 battery ⁵	
Communications 	RTK specifications	
	Data Formats	Leica propriety formats (Leica, Leica Lite, Leica 4G) Optional CMR, CMR+, RTCM 2.1, RTCM 2.3, RTCM 3.0, RTCM 3.1
	RTK baseline	Optional 5 km maximum baseline or unlimited baseline lengths
	Position update rate	1 Hz standard. Optional 5 Hz (0.2 sec)
	Network Rover	VRS, FKP, iMAX, MAX, Nearest station
	External Devices	
	Radio Modem	Satellite and Pacific Crest radios in GFU housing (connected using GHT56 SmartHolder)
	Mobile Phone	<ul style="list-style-type: none"> GSM / CDMA modules in GFU housing (connected using GHT56 SmartHolder) <i>Bluetooth</i>[®] mobile phones
	GS09 antenna	<ul style="list-style-type: none"> <i>Bluetooth</i>[®] USB Cable
	PC with Microsoft Windows	<ul style="list-style-type: none"> USB data cable CF-card reader
Internet	Mobile phone using FTP protocol	

¹ Measurement precision and accuracy in position and accuracy in height are dependent upon various factors including number of satellites, geometry, observation time, ephemeris accuracy, ionospheric conditions, multipath etc. Figures quoted assume normal to favorable conditions. Times required are dependent upon various factors including number of satellites, geometry, ionospheric conditions, multipath etc. GPS and GLONASS can increase performance and accuracy by up to 30% relative to GPS only.

² May vary due to atmospheric conditions, multipath, obstructions, signal geometry and number of tracked signals.

³ Compliance with ISO9022-10-08, ISO9022-11-special and MIL-STD-810F Method 502.4-II, MIL-STD-810F Method 501.4-II

⁴ Compliance with ISO9022-13-06, ISO9022-12-04 and MIL-STD-810F Method 507.4-I

⁵ May vary with temperature and battery age.